Validation of High-Resolution, Multi-Satellite Sea Surface Temperature

T. MIKE CHIN, JORGE VAZQUEZ, EDWARD M. ARMSTRONG

Jet Propulsion Laboratory, California Institute of Technology Pasadena, California

Multi-sensor Ultra-high Resolution (MUR) SST Analysis Project Production of high-resolution (1~2 km), daily SST maps from multi-satellite data sets.

Sea Surface Temperature (SST) Data

- Research uses: weather forecasts, global climate, ocean fronts, fishery/bio-productivity, airsea interaction, tropical cyclones, . . .
- Measurements: ships of opportunity, buoys, and satellites, e.g.:

Instrument	Radiometer/Orbit	Resolution	Error	Issues
or Satellite		(km)	(RMS)	
AVHRR	IR/Polar	1	0.6°C	Clouds, aerosols
MODIS	IR/Polar	1	0.4°C	Clouds, aerosols
AATSR	IR/Polar	1	0.3°C	Clouds
AMSR-E	MW/Polar	25	0.5°C	Land, rain
TMI	MW/Equatorial	25	0.5°C	Land, rain
GOES Imager	IR/Geostationary	6	1.0°C	Clouds, aerosols
SEVIRI	IR/Geostationary	6	0.7°C	Clouds, aerosols
MT-SAT-1R	IR/Geostationary	6	$\sim 0.7^{\circ} \mathrm{C}$	Clouds, aerosols

infra-red (IR): since ~1981, higher resolution. *micro-wave* (MW): less prone to weather.

⇒ Single-sensor bias (calibration) data are available in the data format defined by the Group for High Resolution SST (GHRSST).


Multi-Resolution Variational Analysis (MRVA)

MUR will be available through PO.DAAC (JPL) in 2010.

Satellite-based SST data are *irregularly-sampled* by different sensor types. We employ a wavelet-based, multi-resolution analysis technique to ensure consistency of our analysis with the self-similar (power-law) characteristics observed empirically over a wide range of wavenumber spectrum. MRVA:

- performs interpolation at different scales (1/4°, 1/8°, 1/16° ...)
- preserves both long correlations and small-scale features.
- is used for both single-sensor analysis for bias correction and multi-sensor analysis for production.


MRVA Example (interpolate test data)



National Astronautics and Space Administration Jet Propulsion Laboratory California Institute of Technology Pasadena, California


The research described in this poster was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration (NASA).

Comparison to AATSR satellite swaths




RMS errors against AATSR values

Red is AMSRE; blue is MODIS-A; black is 3-sensor combination (AMSRE, MODIS-A & -T) analysis.




Buoy comparison


Interpolated AMSRE and MODIS(Aqua/Terra) data sets are compared against *NDBC moored buoy* data:





over Nov-Dec 2008 and Jan-Mar 2009 periods. 41048: (–69.65,31.98)




RMS difference to buoys in N.W. Atlantic









Summary

- Inter-satellite and buoy comparisons are used to examine:
 - data biases
 - analysis techniques and parameters (e.g., resolution)
- Bias values (in GHRSST files) were useful for combining AMSRE (MW) and MODIS-A/T (IR) data.
- Multi-sensor combination improves agreements with buoys and AATSR data consistently.